



CYCLONE 120 TRAILER

ALL IN ONE SYSTEM FOR BLASTING LARGE & SMALL PROJECTS

The Quill Falcon Cyclone 120 Trailer is both convenient and powerful. It comprises of a Quill Falcon Cyclone 120, a 115 litre water tank and a 177cfm compressor providing customers with everything they need to start blasting almost immediately.

The Quill Falcon Cyclone 120 Trailer is extremely popular with many of our highways customers who are often working in difficult and remote locations where access to a water supply is often limited.

The Quill Falcon Cyclone 120 Trailer takes away the hassle and worry of being held up on site waiting for plant hire companies to deliver compressors and of potentially unreliable water supplies.



DIMENSIONS

Capacity:	121 litres
Height:	1750mm
Width:	1800mm
Depth:	4300mm
Unladen Weight:	1580kg
Laden Weight:	1920kg (garnet)

BLAST MEDIA

Number of 25kg bags to fill vessel	
Garnet:	8 bags
Iron Silicate:	7 bags
Glass:	5 bags

SPECIFICATIONS

Water Tank:	115 litres
Water Consumption:	100 – 200ml per minute
Grit Type:	Standard particle blast media
Grit Consumption:	0.4 – 0.7kg per minute
Grit Refill:	Up to 8 hrs between refills
Air Supply:	177cfm
Air Supply Hose:	2 inch
Blast Hose Size:	1 inch
Blast Hose Max Length:	100m
Blasting Pressure:	20 – 120psi
Compressor Fuel Tank:	50 litres

Weights and dimensions are based on current models in manufacture. Cyclone Trailer System laden weight = full vessel of grit and water and full tank of diesel. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Grit and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.

For more information please call +44 (0) 1332 864664 or email sales@quillinternational.com
 Quill International Group, Castle Lane, Melbourne, Derbyshire, DE73 8JB (UK)