



CYCLONE 60 TRAILER

ALL IN ONE SYSTEM FOR BLASTING SMALL & LARGE PROJECTS

The Quill Falcon Cyclone 60 Trailer is the most convenient of the Quill Falcon range as it comprises of a Quill Falcon Cyclone 60, a 115 litre water tank and a 90 or 140cfm compressor. In essence it provides our customers with everything they need to start blasting almost immediately.

The Quill Falcon Cyclone 60 Trailer takes away the hassle and worry of being held up on site waiting for plant hire companies to deliver compressors and of potentially unreliable water supplies.



DIMENSIONS

Capacity:	58 litres
Height:	1530mm
Width:	2000mm
Depth:	3050mm
Unladen Weight:	1026kg
Laden Weight:	1240kg (garnet)

BLAST MEDIA

Number of 25kg bags to fill vessel	
Garnet:	4 bags
Iron Silicate:	3 bags
Glass:	2 bags

SPECIFICATIONS

Water Tank:	115 litres
Water Consumption:	100 – 150ml per minute
Grit Type:	Standard particle blast media
Grit Consumption:	0.6 – 1kg per minute
Grit Refill:	Up to 3 hrs between refills
Air Supply:	90 or 140cfm
Air Supply Hose:	¾ inch
Blast Hose Size:	1 inch
Blast Hose Max Length:	80m
Blasting Pressure:	20 – 80psi
Compressor Fuel Tank:	50 litres

Weights and dimensions are based on current models in manufacture. Cyclone Trailer System laden weight = full vessel of grit and water and full tank of diesel. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Grit and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.

For more information please call +44 (0) 1332 864664 or email sales@quillinternational.com
 Quill International Group, Castle Lane, Melbourne, Derbyshire, DE73 8JB (UK)