

NEW QUILL FALCON CYCLONE 60



FASTER, DRIER, LESS GRIT & MORE POWER

The Quill Falcon Cyclone 60 is possibly the most versatile of the Quill Falcon Systems as it is powerful, easily portable and blasts for up to 3 hours before it requires refilling.

The Quill Falcon Cyclone 60 is popular with the offshore industry where it is flown across the globe to carry out surface preparation on helipads, completions and oil and gas tubulars, spot repairs for maintenance programmes and coating removal as part of NDT preparation. The Quill Falcon Cyclone 60 System is also widely used by the shipping industry during voyages to carry out maintenance work as ships transport cargo around the worlds waters.



DIMENSIONS	Capacity: 58 litres
	Height: 1070mm
	Width: 620mm
	Depth: 730mm
	Unladen Weight: 138kg Laden Weight: 269kg (garnet)

BLAST MEDIA	Number of 25kg bags to fill vessel
	Garnet: 4 bags
	Iron Silicate: 3 bags
	Glass: 2 bags

SPECIFICATIONS	Water Pressure & Flow: Standard tap pressure & flow
	Water Consumption: 100 – 150ml per minute
	Grit Type: Standard particle blast media
	Grit Consumption: 0.6 – 1kg per minute
	Grit Refill: Up to 3 hrs between refills
	Air Supply: 90 to 250cfm
	Air Supply Hose: ¾ inch or 2 inch
	Blast Hose Size: 1 inch
	Blast Hose Max Length: 100m
	Blasting Pressure: 20 – 100psi

TO DISCUSS YOUR INDIVIDUAL PROJECT REQUIREMENTS PLEASE
CALL THE QUILL INTERNATIONAL GROUP ON +44 (0) 1332 864664

Weights and dimensions are based on current models in manufacture. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Grit and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.