

# NEW QUILL FALCON CYCLONE 60 TRAILER



**FASTER, DRIER, LESS GRIT & MORE POWER**

The Quill Falcon Cyclone 60 Trailer is the most convenient of the Quill Falcon range as it comprises of a Quill Falcon Cyclone 60, a 115 litre water tank and a 90 or 140cfm compressor. In essence it provides our customers with everything they need to start blasting almost immediately.

The Quill Falcon Cyclone 60 Trailer takes away the hassle and worry of being held up on site waiting for plant hire companies to deliver compressors and of potentially unreliable water supplies.



<b>DIMENSIONS</b>	Capacity: 58 litres
	Height: 1530mm
	Width: 2000mm
	Depth: 3050mm
	Unladen Weight: 1026kg
	Laden Weight: 1240kg (garnet)

<b>BLAST MEDIA</b>	Number of 25kg bags to fill vessel
	Garnet: 4 bags
	Iron Silicate: 3 bags
	Glass: 2 bags

<b>SPECIFICATIONS</b>	Water Tank: 115 litres
	Water Consumption: 100 – 150ml per minute
	Grit Type: Standard particle blast media
	Grit Consumption: 0.6 – 1kg per minute
	Grit Refill: Up to 3 hrs between refills
	Air Supply: 90 or 140cfm
	Air Supply Hose: ¾ inch
	Blast Hose Size: 1 inch
	Blast Hose Max Length: 80m
	Blasting Pressure: 20 – 80psi
Compressor Fuel Tank: 50 litres	

TO DISCUSS YOUR INDIVIDUAL PROJECT REQUIREMENTS PLEASE CALL THE QUILL INTERNATIONAL GROUP ON +44 (0) 1332 864664

Weights and dimensions are based on current models in manufacture. Cyclone Trailer System laden weight - full vessel of grit and water and full tank of diesel. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Grit and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.